

Tensorgrip®

4TH GEN

A NEW GENERATION OF STRENGTH
BY AUSTIN HARDWARE & SUPPLY, INC.



AH101

PREMIUM CITRUS ADHESIVE CLEANER


4th Gen by Tensorgrip AH101: a premium citrus-based adhesive cleaner and remover designed for safe and powerful adhesive removal. Ideal for various applications such as surface cleaning, adhesive spray equipment purging, and decal adhesive residue removal, AH101 ensures compatibility with most non-porous materials for hassle-free use. Simplify your adhesive management with 4th Gen by Tensorgrip AH101-reliable, efficient and trusted.

ADVANTAGES

- Slow dry for maximum usability
- Compatible with most plastics
- Pleasant citrus scent
- Convenient for purging adhesive spray equipment
- Fully portable system
- 100% cleaner transfer to surface
- Can be used with most spray guns and hoses

TECHDATA

OPEN TIME

 5-7 minutes

COLOR

 Clear

SUITABLE FOR


 Metal/Aluminum Sheeting


 Standard Laminate

 Concrete

 Plastics

PROPERTIES

 Mist Spray

 Not California Compliant

 CO-REZ™ Technology

 HAPs Free

NOT FOR SALE OR USE IN CALIFORNIA.

*The heat resistance value is for reference only and may vary by application. Users should perform their own tests to ensure suitability.

BROUGHT TO YOU BY:



800.821.3520
sales@austinhardware.com
austinhardware.com

A PRODUCT OF QUIN GLOBAL US, Inc.
5510 F ST, Omaha NE 68117

PH: +1 402 731 3636 | info.us@quin-global.com | www.quiringlobal.com

CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES	
Total Solids	0%
VOC Content	100% by weight (Aerosol); 409 g/L (Canister)
Color	Clear
System Flammability	Flammable
Solvent System	D-Limonene
Open time	5-7 minutes dependent on temperature and humidity
Shelf Life	18 months from date of manufacture
PACKAGING	
650 ml	Aerosol Can
22L	Disposable Canister
REGULATORY	
SCAQMD Rule 1171 Compliant	no

DIRECTIONS FOR USE

FOR SURFACE CLEANING:

1. Test for compatibility in inconspicuous area before use.
2. Hold applicator 6"-10" from surface.
3. Apply generous, even coat of cleaner on the surface.
4. Wait 4-7 minutes before wiping for best cleaning performance.

FOR SPRAY GUN AND HOSE CLEANOUT:

1. Disconnect spray gun and hose from adhesive canister.
2. Immediately connect to cleaner canister, and open canister valve.
3. Flush out spray gun and hose for until clear (approx 45 seconds).
4. Close canister valve and bleed pressure before disconnecting hose.

Canister or aerosol will spray adequately above 60°F and should be kept in a warm area. In the event that the container gets abnormally chilled, freezes or gives poor or sputtering spray, it should be warmed up before continued usage. Warming canister by immersion in warm water is recommended.

Notice! Do not store at temperatures over 120°F.

HANDLING & STORAGE

- Consult Safety Data Sheet prior to use.
- Store between 60°F (15°C) and 120°F (50°C).
- Do not store directly on concrete floor.
- Avoid exposure to direct sunlight.
- Always test product to determine suitability for your particular application prior to use in production.

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.

BROUGHT TO YOU BY:



800.821.3520
 sales@austinhardware.com
 austinhardware.com

A PRODUCT OF QUIN GLOBAL US, Inc.
 5510 F ST, Omaha NE 68117

PH: +1 402 731 3636 | info.us@quin-global.com | www.quinglobal.com